

JPA-1120A/1240A

FRONT VIEW

A.T.T Zone Amplifier



FEATURES

- Optional module slot (JTP-10, JDM-10A, JCDP-10MP, JCDR-10RDS).
- Individual EQ per input.
- Input gain control (microphone line inputs 1~3).
- Phantom power switch inputs.
- Input 1 by Combo/Din-7 (PTT 10).
- Input 2~3 by Combo (mic line).
- Input 4~5 by RCA (line).
- Pre-amp out / amp-in for extension with power amplifiers.
- Recording output RCA.
- Telephone paging and night ringer.
- Priority-switch on Mic 1, 2, 3.

Pack Series

FM/AM Tuner
JTP-10



Digital Message
JDM-10A



CD/MP3 Player
JCDP-10MP



CD/MP3/AM/FM/RDS
Receiver
JCDR-10RDS



SPECIFICATIONS

Input Sensitivity / Impedance	MIC/LINE1~3 : -50dBu(2.45mV) 5K Ω BAL
	-10dBu(245mV) 5K Ω BAL
	LINE 4~5 : -10dBu(245mV) 15K Ω UNBAL
	TEL PAGING : -10dBu(245mV) 5K Ω BAL
	PACK UNIT: -10dBu(245mV) 10K Ω UNBAL
	REC OUT : 0dBu(775mV) 3K Ω UNBAL
	PRE OUT : 0dBu(775mV) 100 Ω UNBAL
AMP IN : 0dBu(775mV) 10K Ω UNBAL	
Rated Output	JPA-1120A : 120W(RMS)
	JPA-1240A : 240W(RMS)
Output Impedance	LOW IMP : 4 Ω
ATT. Step(option)	EUROPE : 100V,70V,50V,25V, 12.5V,8.9V
	AMERICA : 70V,50V,25V, 12.5V, 8.9V, 6V
Frequency Response(line signal)	LESS THAN -3dB(55Hz ~ 16kHz)
Signal to Noise Ratio	LINE : MORE THAN 80dB('A' WEIGHT)
	MIC : MORE THAN 70dB('A' WEIGHT)
T.H.D	LESS THAN 1%(1kHz)
Power Consumption	JPA-1120A : 350W
	JPA-1240A : 630W
1/8 Power Current Draw (120V/230V)	JPA-1120A : 1.6A/0.8A
	JPA-1240A : 2.8A/1.4A
1/3 Power Current Draw (120V/230V)	JPA-1120A : 2.4A/1.2A
	JPA-1240A : 4A/2A
Rated Power Current Draw (120V/230V)	JPA-1120A : 3.6A/1.8A
	JPA-1240A : 6.4A/3.2A
Power source(option)	AC 120V/230V/240V 50/60Hz , DC 24V
Dimensions (mm)	430(W) X 133(H) X 352(D)
	16.9(W) X 5.2(H) X 13.9(D)
Weight (kg/lbs)	JPA-1120A : 13/28.7, JPA-1240A : 14/30.9

Drawing

